

TSK-HR200 (2D Scanner)



- **PERFORMANCE**

CPU : 32 Bit RISC,
Image Sensor : 752 * 480 CMOS
Target Distance : 4 ~ 30 Cm from the camera face
Viewing Angle Horizontal : 45°, Vertical 45°
Symbologies : 2D:PDF417, QR Code, DataMatrix, Aztec, Maxi, Lpcode, Hot code, etc.
1D:Code128, EAN-13 ,EAN-8 ,Code39, UPC-A ,UPC-E, Codabar, China post 25, Interleaved2 of5, ISBN/ISSNCode 93 etc.
Interface : RS-232C, HID USB, Serial USB

- **MECHANICAL**

Dimensions : 73mm X 126mm X 163mm
Weight : 250g
Cable Length : RS232C: 1.8M(6 ft), USB: 2M(6.6 ft).
Body Material : ABS Plastic

- **ELECTRICAL**

Power Supply : +4.75 to 5.25V, Typical 300mA,
Peak 350mA
Standby Current : 50mA (5 VDC)

- **DURABILITY**

Trigger Switch : 1 million Actuations
Cable : 100,000 Bending at 90 degree with 500g weight
Shock Resistance : 1.8 meter drop onto Concrete Surface

- **ENVIRONMENTAL**

Temperature : Operating : 0 ~ 50°C,
Storage : -20 ~ 65°C
Humidity : Operating : 10% ~ 80%,
Storage : 0% ~ 95%
Certification : FCC Part15 Class B & CE EMC Class B