

# TSK-5000P

## ( 1D, 2D BARCODE SCANNER )



- PERFORMANCE**

**CPU :** 32Bit  
**Scan rate :** 32 Scans Per Second  
**Resolution :** 4 mil (0.1mm)  
**Photo Sensor :** 1280 \* 800 CMOS  
**Illumination :** 630nm Visible Red LEDS  
**Skew Angle :** ±55 Degree  
**Pitch Angle :** ±55 Degree  
**Field of View :** Horizontal 39°, Vertical 24°  
**Field Width :** 100mm (15mil)  
**Depth of field :** 30~365mm  
  
**Symbologies :**

- 1D :** UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code93, GS1...
- 2D :** PDF417, Data Matrix QR Code...

- Interface :** USB, RS-232, PS2, Serial USB

**Mobile QR Code**



- MECHANICAL**

**Dimensions :** L x W x H: 95mm x 70mm x 160mm  
**Weight :** 153g  
**Body Material :** ABS Plastic

- ELECTRICAL**

**Power Supply :** 5V  
**Power Consumption :** MAX330mA

- DURABILITY**

**Trigger Switch :** 1 million Actuations  
**Shock Resistance :** 1 meter drop onto Concrete Surface

- ENVIRONMENTAL**

**Temperature :** Operating : -5 ~ 50°C, Storage : -20 ~ 60°C  
**Humidity :** Operating : 10% ~ 80%, Storage : 10% ~ 95%  
**Mechanical Shock :** Functional after 1.5m (5ft) drops  
**ESD Protection :** Functional after 15kV discharge



(주)테크스캔코리아