

TSK-5100

(1D, 2D BARCODE SCANNER)



- PERFORMANCE**

CPU : 32Bit
Scan rate : 32 Scans Per Second
Resolution : 4 mil (0.1mm)
Photo Sensor : 1280 * 800 CMOS
Illumination : 630nm Visible Red LEDs
Skew Angle : ±55 Degree
Pitch Angle : ±55 Degree
Field of View : Horizontal 39°, Vertical 24°
Field Width : 100mm (15mil)
Depth of field : 30~365mm

Symbologies : **1D :** UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code93 , GS1...

2D : PDF417, Data Matrix
 QR Code...

- Interface :** USB, RS-232, PS2, Serial USB

Mobile QR Code



- MECHANICAL**

Dimensions : 173mm*67mm*94mm(L*W*H)
Weight : 220g With Cable
Body Material : ABS Plastic

- ELECTRICAL**

Power Supply : 5V
Power Consumption : MAX330mA

- DURABILITY**

Trigger Switch : 1 million Actuations
Shock Resistance : 1 meter drop onto Concrete Surface

- ENVIRONMENTAL**

Temperature : Operating : -5 ~ 50°C, Storage : -20 ~ 60°C
Humidity : Operating : 10% ~ 80%, Storage : 10% ~ 95%
Mechanical Shock : Functional after 1.5m (5ft) drops
ESD Protection : Functional after 15kV discharge



(주)테크스캔코리아