

TSK-5700

(1D, 2D BARCODE SCANNER)



• PERFORMANCE

CPU : 32Bit
Scan rate : 60 Scans Per Second
Resolution : 3 mil (0.1mm)
Photo Sensor : 1280 * 800 CMOS
Illumination : 630nm Visible Red LEDs
Skew Angle : ±60 Degree
Pitch Angle : ±60 Degree
Field of View : Horizontal 48°, Vertical 30°
Field Width : 120mm (15mil)
Depth of field : 30~250mm

Symbologies :

1D : UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code93 , GS1...

2D : PDF417, Data Matrix QR Code...

• **Interface :** USB, RS-232, Serial USB

Mobile QR Code



• MECHANICAL

Dimensions : 100mm * 82mm * 150(L*W*H)
Weight : 200g With Cable
Body Material : ABS Plastic

• ELECTRICAL

Power Supply : 5V
Power Consumption : MAX400mA

• DURABILITY

Trigger Switch : 1 million Actuations
Shock Resistance : 1 meter drop onto Concrete Surface

• ENVIRONMENTAL

Temperature : Operating : -5 ~ 50°C, Storage : -20 ~ 60°C
Humidity : Operating : 10% ~ 80%, Storage : 10% ~ 95%
Mechanical Shock : Functional after 1.5m (5ft) drops
ESD Protection : Functional after 15kV discharge



TechScan

(주)테크스캔코리아