

TSK-1920 (유/무선, 메모리 겸용 2D 스캐너)



수신 동글 1EA 스캐너 4EA 연결 가능

• PERFORMANCE

CPU : 32Bit
Scan rate : 36 Scans per Second
Resolution : 4 mil (0.1mm)
Photo Sensor : 752 * 480 Pixel CMOS
Illumination : 660nm Visible Red LEDS
Field Width : 100mm
Depth of field : 30 ~ 280mm
Symbologies : UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code93, GS1, 2D BARCODE

Interface : USB-HID, 메모리 방식, 동글 적용

• Wireless

Carrier Frequency : 2.4GHz RF Transceiver
Modulation Method : GFSK, 1Mbps
Hopping : 1600 hops/sec, 1MHz channel space
Receiving Signal Range : -84 to -20dbm
Receiver IF Frequency : 1.5MHz center frequency
Radio Range : 40M open air

• MECHANICAL

Dimensions : 95mm x 70mm x 160mm
Weight : 184g
Body Material : ABS Plastic

• ELECTRICAL

Power Supply : 5VDC \pm 5%
Power Consumption : stand by 3mA Max 140mA
Battery Life : **Up to 10,000 Scans**

• DURABILITY

Trigger Switch : 1 million Actuations
Shock Resistance : 1 meter drop onto Concrete Surface

• ENVIRONMENTAL

Temperature : Operating : 0 ~ 50°C, Storage : -10 ~ 60°C
Humidity : Operating : 10% ~ 95%, Storage : 10% ~ 95%
Mechanical Shock : Functional after 1.5m (5ft) drops
ESD Protection : Functional after 15kV discharge