

TSK-5100 OTG

(1D, 2D BARCODE SCANNER)



• PERFORMANCE

CPU : 32Bit
Scan rate : 60 Scans Per Second
Resolution : 3 mil (0.075mm)
Photo Sensor : 1280 * 800 CMOS
Illumination : 610nm Visible White LEDS
Skew Angle : ±55 Degree
Pitch Angle : ±55 Degree
Field of View : Horizontal 51°, Vertical 32°
Field Width : 150mm (13.5mil)
Depth of field : 30~450mm

Symbologies : **1D :** UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code93 , GS1...
2D : PDF417, Data Matrix, QR Code, OCR...

Interface : USB HID, USB COM

Mobile QR Code



• MECHANICAL

Dimensions : 173mm*67mm*94mm(L*W*H)
Weight : 220g With Cable
Body Material : ABS Plastic

• ELECTRICAL

Power Supply : 스마트폰 USB C Type
Power Consumption : MAX330mA

• DURABILITY

Trigger Switch : 1 million Actuations
Shock Resistance : 1 meter drop onto Concrete Surface

• ENVIRONMENTAL

Temperature : Operating : -5 ~ 50°C, Storage : -20 ~ 60°C
Humidity : Operating : 10% ~ 80%, Storage : 10% ~ 95%
Mechanical Shock : Functional after 1.5m (5ft) drops
ESD Protection : Functional after 15kV discharge



Techscan

(주)테크스캔코리아