

TSK-1000M



PERFORMANCE

Scan rate :	125 ~ 200 Scans per Second
Resolution :	4mil (0.1mm)
Photo Sensor :	20480 Pixel Linear CCD
Illumination :	660nm Visible Red LEDS
Field Width :	95mm
Depth of field :	40~100mm
Symbologies :	UPC/EAN/JAN, Code39, Interleaved 2 of 5 Standard 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, Code128, MSI, Plessey, Code39, Code 3 of 5 (Korean Postage)
Interface :	IBM PC AT/XT/PS2 Keyboard wedge, USB, Standard RS-232C, TTL Serial, Wand Emulation,

MECHANICAL

Dimensions :	56mm X 60mm X 29.5mm
Weight :	75g
Cable :	2m Straight Fixed to Scanner
Body Material :	PC + Fiber

ELECTRICAL

Power Supply :	5VDC \pm 5%
Current Active :	30mA ~ 100mA

DURABILITY

Trigger Switch :	1 million Actuations
Cable :	100,000 Bending at 90 degree with 500g weight
Shock Resistance :	1 meter drop onto Concrete Surface

ENVIRONMENTAL

Temperature :	Operating : 0 ~ 50°C, Storage : -10 ~ 60°C
Humidity :	Operating : 10% ~ 80%, Storage : 10% ~ 95%
Mechanical Shock :	Functional after 1.5m (5ft) drops
ESD Protection :	Functional after 15kV discharge