

TSK-200(Aluminum)/250(Plastic)



PERFORMANCE

MODEL :	TSK200 (TSK-200T(TTL), TSK-200K(K/W), TSK-200R(RS-232), TSK- 200U(USB) TSK-250T(TTL), TSK-250K(K/W), TSK-250R (RS-232)
INTERFACE :	TSK-200(TTL, K/W, RS232, USB) / TSK-250(TTL, K/W, RS232)
RESOLUTION :	4mil(0.10mm)
SCAN SPEED :	2~40ips
PCS :	0.6 ~ 0.9
DOF :	10~80mil
AMBIENT LIGHT REJECTION :	3000LUX
SYMBOLGIES :	UPC/ENA/JAN, CODE39 INTERLEAVED 2OF 5,STANDARD2OF5,MATRIX5, CODABAR,COED128,INDUSTRIAL2OF 5,CODE93,CODE3 OF5
OPTIONAL :	INFRARED (940NM) OR VISIBLE RED(660NM) MODULE,PARTS SUPPLY AVAILABLE(TSK-250 SERIES ONLY)

ELECTRICAL

POWER CONSUMPTION :	TSK-200(12mA, 75mA, 75mA,75mA) / TSK-250(5mA, 37mA, 37mA)
POWER SUPPLY :	TSK-200(K/W, USB : DC5V±10% DC5V±10% RS-232 : DC6V~9V 300mA) / TKS-250(DC 5V±10% DC5V±10% DC5V±10%)

MECHANICAL

CASE :	TSK-200(Aluminum) / TSK-250(ABS PLASTIC)
DIMENSIONS :	TSK-200(125X52X30mm) / TSK-250(100X34X28mm)
WEIGHT(W/O CABLE) :	TSK-200(530g, 550g, 550g, 550g) / TSK-250(52g, 66g, 66g)